– Proposal —

SOUTHEAST ELECTRICAL CONTRACTORS, INC. P.O. Box 1849 CALLAHAN, FLORIDA 32011-1849 (904) 879-4226

1177

of

PROPOSAL SUBMITTED TO	PHONE	DATE
Nassau County Board Of County Con	mmissioners	7-3-96
		this Issaus Disla Timbriss
C/O T. J. Greeson, P.O. Box 1010 CITY, STATE and ZIP CODE	JOB LOCATION	ttle League Field Lighting
Fernandina Beach, FL 32034		
ARCHITECT DATE OF PLANS		JOB PHONE
We hereby submit specifications and estimates for:		
Lighting of the Little Le	eague field accord	ing to specifications
	eague Lieiu accord	Ing to specifications.
	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
		,
Ma Menerga havebute furnish metarial and le	ahar aamalata in aasardana	as with above appointing for the own of
መደ 	abor — complete in accordance	
		dollars (\$ 38,150°°).
Payment to be made as follows:		
		\wedge
All material is guaranteed to be as specified. All work to be completed in a	workmanlike	
manner according to standard practices. Any alteration or deviation from above	specifications Authorized Signature	ST 1/mil
involving extra costs will be executed only upon written orders, and will become charge over and above the estimate. All agreements contingent upon strike	es, accidents	reaccel mouths
or delays beyond our control. Owner to carry fire, tornado and other necessal Our workers are fully covered by Workman's Compensation Insurance.	ry insurance. Note: This pr withdrawn by us if not a	roposal may be accepted within days.
Acceptance of Proposal — The above prices, sp	pecifications \(\simeq \)	
and conditions are satisfactory and are hereby accepted. You are	authorized Signature	J D Some
to do the work as specified. Payment will be made as outlined at	pove.	- 15
Date of Acceptance:	Signature	-
		//

CALLAHAN LITTLE LEAGUE BASEBALL FIELD SPECIFICATIONS

- 1) Lighting of 2 200' minor league fields.
- 2) The lighting level requirements on the field will be 30 footcandles on the infield and 20 footcandles on the outfield.
- 3) The lighting shall be a total of 40 fifteen hundred watt metal halide General Electric sports lights with a five year warranty including parts and labor. Lamps shall be warranted for two years, the first year parts and labor, the second year parts only.
- 4) All poles will be concrete. Infield mounting heights should be 40'. Outfield mounting heights should be 50'.
- 5) Contractor shall furnish poles, light fixtures, galvanized cross arms and all mounting hardware.
- 6) Contractor shall furnish a 400 amp 1 phase electrical service raintight on galvanized service pedestal.
- 7) Contractor shall wire poles to service location according to the attached chart.
- 8) Contractor shall assemble, aim and wire fixtures using the attached chart.
- 9) Contractor shall provide verification that pole and location will meet or surpass the minimum requirements for lighting, set backs and heights as they apply to: Minor League Baseball.
- 10) Contractor should coordinate light fixture voltages with local power company prior to fixture installation.
- 11) Contractor shall coordinate service location, transformer location and all utility needs with local power company.
- 12) All cable to fixtures will be sun resistant and will enter fixture through a rain tight fitting.
- 13) All cables will be copper as well as THHN or equal and stranded.
- 14) All cross arms and hardware on poles will be hot dipped galvanized.

- 15) Each pole will be grounded at base with one 10' ground rol.
- 16) All underground electrical will be installed in conduit according to local codes.
- 17) Contractor will be responsible for pulling all permits as required by county.
- 18) All work will be performed in a professional manner with qualified personnel.

CALLAHAN LITTLE LEAGUE POLE AND FIXTURE CHART

POLES	MOUNTING HEIGHTS	FIXTURES	K.W.	CONDUCTOR SIZE BACK TO SERVICE LOCATION
A1	40 M.H.	3	4.9	#10
A2	40 M.H.	3	4.9	#10
B1	50 M.H.	7	11.4	#6
B2	50 M.H.	7	11.4	#6

POLES	CONDUIT	BREAKER SIZE	
A1	3/4"	2-POLE 30 AMP	
A2	3/4"	2-POLE 30 AMP	
B1	1"	2-POLE 60 AMP	
B2	1"	2-POLE 60 AMP	

TYPICAL FOR BOTH FIELDS